

# MOLYSULF®

GREASE | FLUID LIKE FOR GEARBOX LUBRICATION



Product	Benefits / Applications	Type	NLGI Grade	Operating Temperature °C
<b>LL 100</b>  Heavy Duty Fluid Grease for Closed Gearboxes	<ul style="list-style-type: none"> <li>• Forms a solid lubricating film to provide emergency lubrication.</li> <li>• Prevents metal-to-metal contact and reduces friction and wear.</li> <li>• Withstands extremely high loads.</li> <li>• Highly resistant to hot or cold water and water washout.</li> <li>• Extends relubrication intervals and cuts down lubricant consumption.</li> <li>• Combination of EP additives and solid film lubricants increase the load bearing capacity and provide emergency running in and boundary lubrication.</li> <li>• Use successfully for lubrication of closed gears operating under high stress and humid conditions.</li> </ul>	blue black mineral oil lithium soap thickener EP additive solid lubricants adhesion improver  <b>Packaging</b> 1 kg 5 kg 30 kg 180 kg	00	-30 to +110
<b>LL 100 (SP)</b>  Heavy Duty Fluid Grease for Closed Gearboxes	<ul style="list-style-type: none"> <li>• Forms a solid lubricating film to provide emergency lubrication.</li> <li>• Prevents metal-to-metal contact and reduces friction and wear.</li> <li>• Withstands extremely high loads.</li> <li>• Highly resistant to hot or cold water and water washout.</li> <li>• Extends relubrication intervals and cuts down lubricant consumption.</li> <li>• Combination of EP additives and solid film lubricants increase the load bearing capacity and provide emergency running in and boundary lubrication.</li> <li>• Use successfully for lubrication of closed gears operating under high stress and humid conditions.</li> </ul>	blue black mineral and synthetic oil lithium soap thickener EP additive MoS <sub>2</sub> & solid lubricants adhesion improver  <b>Packaging</b> 30 kg	00	-30 to +110
<b>WG 670</b>  Synthetic Fluid Grease for Gearboxes	<ul style="list-style-type: none"> <li>• For 'long-life' lubrication of gear boxes for 'filled for life' features allowing long term, trouble free maintenance and operation.</li> <li>• For lubrication of worm gear drives for its inherent ability to lower frictional losses, keep temperatures low and for allowing maximum power transmission delivery without overheating.</li> <li>• Especially suited for gear boxes where worm gears are in a combination of steel and tin-bronze materials.</li> <li>• Highly suitable for use in other enclosed gear boxes with spur, helical or spiral bevel trains.</li> </ul>	light tan, beige synthetic oil lithium soap thickener  <b>Packaging</b> 5 kg 30 kg	00	-30 to +130