

MOLYSULF®

GREASE | HEAVY DUTY



Product	Benefits / Applications	Type	NLGI Grade	Drop Point °C	Operating Temperature °C	Packaging
BRB 2EP Universal High Performance Grease with MoS ₂	<ul style="list-style-type: none"> • Heavy duty lithium grease with micro size molybdenum disulfide lubricating solids. • Forms a film to provide emergency lubrication. • Prevents premature bearing failures caused due to lubricant starvation as a film of solid lubricants is always maintained between sliding surfaces. • Prevents metal-to-metal contact, reduces friction and wear. • Protects against fretting corrosion. • Highly resistant to hot or cold water and water washout. 	black mineral oil lithium soap MoS ₂ adhesion improver Organo moly complex additives	2	+185	-30 to +130 (short peaks up to +150)	1 kg 5 kg 30 kg 180 kg
BRB 770 Heavy Duty High Impact Resistant Grease	<ul style="list-style-type: none"> • Prevents metal-to-metal contact, reduces friction and wear & protects against fretting corrosion. • Highly resistant to hot or cold water and water washout. • Extends re-lubrication intervals and cuts down lubricant consumption. • Combination of EP additives increase the load bearing capacity and provide emergency running in and boundary lubrication. • Offers good surface protection and corrosion inhibiting properties. • Very good performance under moderate to high loads and medium speeds under reciprocating motions. 	red mineral oil lithium soap EP additives	2	+190	-7 to +150	1 kg 5 kg
GR 20 Heavy Duty Graphite Grease	<ul style="list-style-type: none"> • As a general purpose, low friction lubricant for gears, rods, chains, guides, chucks, drills, dies, punches, sleeves, cams, bearings, wire ropes, valves, gaskets to prevent wear, binding, sticking, seizure and galling. • For nuts, studs, bull plugs, tubing, pipes, couplings, flanges, fittings, u-bolts, elbow joints to provide an effective seal and prevent seizure. For lubrication of seam welding and ERW machines. 	black mineral oil lithium soap graphite EP additives	2	+180	0 to +180	30 kg 180 kg
LL 102 High Pressure Long Life Grease with MoS ₂	<ul style="list-style-type: none"> • Forms a film to provide emergency lubrication and prevents premature bearing failures caused due to lubricant starvation as a film of solid lubricants is always maintained between sliding surfaces. • Capable of withstanding high pressures. • Highly resistant to hot or cold water and water washout. • Use successfully for roller bearing, all types of anti-friction bearings, plain bearings, roller guides, threaded spindles, splined shafts, taper bearings, needle roller bearings, sliding and mating surfaces under vibratory or reciprocating motions. 	black mineral oil lithium soap MoS ₂ adhesion improver Organo moly complex additives	2	+185	-20 to +130 (short peaks up to +150)	1 kg 5 kg 30 kg 180 kg