

# MOLYSULF®

GREASE | FOR WIRE ROPES, STEEL CABLES, CHAINS



Product	Benefits / Applications	Type	NLGI Grade	Operating Temperature °C
<b>RL 1</b>  Non Melt, Fluid Grease with MoS <sub>2</sub>	<ul style="list-style-type: none"> <li>Highly adhesive, semi fluid extreme pressure grease for lubrication and corrosion protection of wire ropes and steel cables operating under adverse conditions of load, temperatures or environment.</li> <li>Protects against heavy loads, galling and seizing</li> <li>Solid lubricant withstands high loads and pressures</li> <li>Reduces wear and friction</li> <li>Resists vibratory shocks</li> <li>Does not break down or fling under prolonged use</li> </ul>	blue black ISO VG 460 mineral oil non soap thickener corrosion inhibitor  <b>Packaging</b> 400 ml aerosol 5 kg 30 kg 170 kg	00	-25 to +150
<b>CHAIN &amp; WIRE ROPE (SP)</b>  EP Fluid Grease with MoS <sub>2</sub>	<ul style="list-style-type: none"> <li>Highly adhesive, semi fluid extreme pressure grease for lubrication and corrosion protection of wire ropes and steel cables operating under adverse conditions of load, temperatures or environment.</li> <li>Protects against heavy loads, galling and seizing</li> <li>Solid lubricant withstands high loads and pressures</li> <li>Reduces wear and friction</li> <li>Resists vibratory shocks</li> <li>Does not break down or fling under prolonged use</li> </ul>	blackish ISO VG 460 mineral oil lithium complex thickener corrosion inhibitor  <b>Packaging</b> 5 kg 30 kg 180 kg	00	-20 to +130
<b>CHAIN &amp; WIRE ROPE (HD)</b>  EP Fluid Grease with MoS <sub>2</sub>	<ul style="list-style-type: none"> <li>Highly adhesive, semi fluid extreme pressure grease for lubrication and corrosion protection of wire ropes and steel cables operating under adverse conditions of load, temperatures or environment.</li> <li>Protects against heavy loads, galling and seizing</li> <li>Solid lubricant withstands high loads and pressures</li> <li>Reduces wear and friction</li> <li>Resists vibratory shocks</li> <li>Does not break down or fling under prolonged use</li> </ul>	blackish ISO VG 1000 mineral oil lithium complex thickener corrosion inhibitor  <b>Packaging</b> 5 kg 30 kg 180 kg	00	-20 to +130