

PRODUCT INFORMATION



CS 70

CLEANER / DEGREASER

Non Flammable Heavy Duty Cleaner / Degreaser for Cleaning Bearings & Mechanical Parts

Product Description

ASV® CS 70 is a non-flammable, non-conductive, safe, solvent cleaner cum degreaser for all mechanical components. It is a fast acting and fast penetrating cleaner which effectively removes soils, dirt, oxides, silicones, oils & greases and evaporates quickly to enable equipment to be used faster and avoid costly downtime. It quickly penetrates tight spaces and minute crevices to dislodge contaminants through its superior high powered cleaning action and has a distinct advantage over flammable cleaners of having no flash point thereby increasing usage safety. ASV® CS 70 contains no 1,1,1-Trichlorethane or any ozone depleting chemicals.

Applications

For cleaning & degreasing of all kinds of mechanical components such as bearings, gears, sprockets, chains, pulleys, slides, nuts, screws, fasteners, pins, hinges, locks. Also useful for degreasing Corrosion inhibiting compounds from metal surfaces.

Benefits

- Fast penetrating & cleans equipment fast
- Nonabrasive & non flammable
- Non staining and non-corrosive
- Evaporates leaving no residue
- High powered cleaning action
- Non staining & safe on all metals
- Contains safe non-flammable CO₂ propellant
- 360° Valve enables product to be sprayed in any
- position even upside down

Directions for Use

Spray liberally on the surface to be cleaned till the cleaning agent runs off as clear. Use extension tube for hard to reach areas. Use an abrasive or brush to clean heavy oxides or other deposits. Spray starting at the top and finishing at the bottom. Test on plastics by using on a small area before use.



PRODUCT INFORMATION



CS 70

CLEANER / DEGREASER

TECHNICAL PROPERTY			
Parameter*		Value	
Туре		Heavy duty cleaner & degreaser	
Appearance		Liquid	
Color		Clear	
Odor		Mild	
Specific Gravity @ 20°C	g/cm³	1.24 -1.64	
Flash Point	°C	None	ASTM D 56
Boiling Point	°C	87.2	
Solubility		Slight in water	
Vapor Density		4.55	
Percent Volatile	%	100	
Evaporation Rate		fast	
Kauri Butanol Value (KB)		130	ASTM D 1130
Propellant		CO_2	

^{*} of active ingredients

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by ASV Multichemie Private Limited W 46, TTC Industrial Area, MIDC Rabale, Navi Mumbai 400 701 INDIA Contact: +91 22 2764 2516 Email: info@asvmultichemie.com

Available Packaging

575 g / 400 ml aerosol spray

Shelf Life

24 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.