

FM 279

SPRAY

Food Grade Chain Lube

Product Description

FM 279 food grade chain lube is formulated employing high purity USP grade white oils along with a blend of premium food grade additives for enhancing protection against oxidation, corrosion and wear.

FM 279 food grade chain lubricant reduces friction and wear, increases service life of the equipment and cuts down lubrication costs by increasing re-lubrication intervals.

FM 279 food grade chain is formulated using nontoxic ingredients and food grade additives and meets FDA and NSF H-1 requirements for materials that may have incidental food contact as defined under Title 21 CFR 178.3570

Uses / Application

Sprockets, chains, links, pins, bushings, forklift chains, packaging equipment and many more industrial applications

Benefits

- **NSF H-1 Registration Certificate # 158629**
- Penetrates and lubricates effectively to reduce and protect from wear
- Excellent extreme pressure protection
- Outstanding thermal and oxidative stability
- Superior additives provide excellent load carrying
- Increases service life of equipment
- Reduces maintenance costs and downtime

Directions for Use

Clean and degrease the chain completely off old oil, grease, dirt or varnish like residues and anti-corrosion coatings. Spray FM 279 Chain Lube and wait for about 10 minutes for the lubricant to penetrate to all the points. Wipe off excess lubricant from the chain if it is likely to operate under dusty environments.

Caution

Contains flammable propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

FM 279

SPRAY

TECHNICAL PROPERTY			
Parameter	Value	Unit	Standard
Appearance	Oily liquid		
Color	Clear, colorless		
Odor	Odorless		
Viscosity @ 40°C	100	mm ² /s	ASTM D 445
Viscosity @ 100°C	12	mm ² /s	ASTM D 445
Flash point	+200	°C	ASTM D 92
Pour point	-10	°C	ASTM D 97
Service temperatures	-10 to +165	°C	
Propellant (aerosol only)	Hydrocarbon		
Approvals	NSF Registration Certificate # 158629		

* of active ingredients

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

500 ml aerosol spray

Shelf Life

24 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.