



ASA 200 RW

Formulated Specially For Robotic Welding Applications

Product Description

ASV® ASA 200 RW is a synthetic anti stick separation agent for preventing adherence of spatter to insides of robotic welding nozzles.

It does not contain any silicones or ozone depleting chemicals and is paintable.

Applications

For prevention of spatter formation during robotic welding applications.

Benefits

- Prevents burning of welding spatters on contact tips & work pieces
- Provides long lasting anti adherent effect
- Special viscosity makes it easy for application by mist type atomization or by dipping method.
- Extends nozzle life
- Silicone free

Directions for Use

Use as supplied. Never dilute or mix with other oil or grease.

ASA 200 RW

TECHNICAL PROPERTY	
Parameter	Value
Type	Anti-spatter agent
Appearance	Oily lubricant
Color	Water white
Type of film	Nondrying, oily
Flash point °C	None
Density @ 20°C, g/cm ³	0.975-1.05
Vapor density	Not applicable
Solubility in water	Insoluble

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

5 liter , 30 liter

Shelf Life

12 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.