

KL 250

OIL

Non Carbonizing Synthetic Oil For Lubrication of Chains Operating At High Temperatures

Applications

High speed tenter frames in textile industry, glass works, paint booths, automotive assembly lines, varnish curing booths, open chains in industry, steel plants, paper and plywood manufacturing units, ceramic processing plants, latex manufacturing plants, lubrication of all chains, clips, bearings

Directions for Use

Use as supplied. Never dilute or mix with other oil or grease.

For optimal lubrication and adhesion, clean and degrease the surface of all previous residues, lubricants or contaminants. Apply to clean surface by regular oiling methods i.e. by brushing, spraying, dipping or drop feed oiling mechanisms. Allow time for lubricant to penetrate and excess lubricant to drip off before restarting operations.

For new chains: Thoroughly clean prior to applying this lubricant. It is recommended to keep new chains dipped in the lubricant for 30 minutes to ensure complete penetration to all innermost points. Avoid excessive use. Use as per instructions laid down in manufacturers manual. Replace cap after use.

Benefits

- Extremely wide service temperature range from -25 to +225°C
- Very good extreme pressure properties enhance load carrying abilities and reduces frictional wear
- Extremely low evaporation rate at high temperatures
- Absolute synthetic formulation benefits in terms of no carbon or resinous deposit even at high temperatures
- Reduces cost related to chain cleaning such as labor, production loss and downtime
- Lower evaporation rate reduces consumption and allows for extension of lubrication periods thereby cutting down on lubrication costs
- Provides superior lubrication and protection even when subjected to high temperatures and humid conditions
- Due to superior lubrication, power requirements are reduced resulting in both lubricant as well as energy savings
- Cost savings due to reduction of premature wearing out of parts and replacements are also greatly increased
- Good adhesive properties and water resistant

KL 250

OIL

TECHNICAL PROPERTIES			
PARAMETER	VALUE	UNIT	METHOD
Appearance	Oily liquid		Visual
Color	Yellowish		Visual
Base oil viscosity @ 40°C	250	mm ² /s	ASTM D 445
Base oil viscosity @ 100°C	21	mm ² /s	ASTM D 445
Density	0.92-0.98	g/cc	In house
Flash point	+278	°C	ASTM D 92
Pour point	-25	°C	ASTM D 97
Service temperature range	-25 to +225	°C	In house
Copper strip corrosion test	1a, pass	Rating	ASTM D 4048
Conradson carbon residue	Lesser than 0.01	% by wt.	ASTM D 189
Evaporation, 24 hours / 200° C	3	% max	In house

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

5 liter, 30 liter, 200 liter

Shelf Life

36 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.